Always check our website for the most updated specifications: www.zumacollection.com



CODES AND COMPLIANCE

Products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8

ELECTRICAL REQUIREMENTS

We recommend one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

DIMENSIONS

74" x 44" x 23"

Whirlpool Operating Gallons: 70

Gallons to Overflow: 95 Material: Acrylic

Combination **Whirlpool** (pump and blower location only) Airbath System II

Chromotherapy Light **Grab Bars High Density Insulation** iBath Sound System Lo-Profile Tub Edge Ozone System (Whirlpool and/or Airbath only) Pillow -12" **Rotary Jets** Thermal Comfort System (TCS must be at opposite end if used with VSM) Trim Kit Upgrade Vibro Sonic Massage (VSM must be at opposite

OPTIONAL

ACCESSORIES

end if used with TCS)

Waste & Overflow Linear Overflow

Undermount

INSTALLATION TIPS

SUCTION

LEGEND:

SYLLENT

· Install product according to Owners manual and local codes.

B BLOWER

SJET

ACCESS PANEL (MINIMUM 16" X 20")

- All whirlpool or Airbath[®] units require an access panel.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.
- Cut-out dimensions: Zuma recommends you wait until you have the actual unit or contact us for a template.

ON/OFF CONTROL