


Always check our website for the most updated specifications: www.zumacollection.com



All bathtub dimensions are $\pm 1/2"$.

CODES AND COMPLIANCE

Products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories - Canada (cUL)
- ANSI Z124.1 • ANSI A112-19.7
- ANSI A112.19.8

ELECTRICAL REQUIREMENTS

We recommend one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bath-


DIMENSIONS

60" x 30" x 22"


Whirlpool Operating Gallons: 40

Gallons to Overflow: 65



Whirlpool



Combination (pump and blower location only)



Airbath System II



OPTIONAL ACCESSORIES

- Chromotherapy Light
- Grab Bars
- High Density Insulation
- iBath Sound System
- Ozone System
(Whirlpool and/or Airbath only)
- Pillow -12" - Angle
- Rotary Jets
- Thermal Comfort System
(TCS can not be used with VSM)
- Trim Kit Upgrade
- Vibro Sonic Massage
(VSM can not be used with TCS)
- Waste & Overflow upgrade:
 - Cable Drive Waste & Overflow
 - Linear Overflow

Undermount Yes No

INSTALLATION TIPS

- Install product according to Owners manual and local codes.
- All whirlpool or Airbath[®] units require an access panel.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.
- Dimensions for undermount installations should be taken directly from the bathtub.
- Cut-out dimension: 58" x 28"